

View Online at <https://aerobasegroup.com/nsn/5306-00-508-3241>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.438 inches and 1.531 inches

**Fastener Length:**

Between 1.500 inches and 1.562 inches

**Head Style:**

Crowned hexagon

**Head Height:**

0.109 inches

**Width Between Flats:**

Between 0.365 inches and 0.377 inches

**Hole Diameter:**

0.035 inches

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.031 inches and 0.062 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Product Name:**

Navy special project

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas428 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.