NSN 5306-00-508-4662

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-4662

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.345 inches and 0.395 inches |
| Fastener Length: |
| Between 0.855 inches and 0.885 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.051 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.490 inches and 0.510 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 20205 nac6204 professional/industrial association standard |

NSN 5306-00-508-4662

Shear Bolt - Page 2 of 2



| | L - | 11 | | ife | _ |
|---|------------|----|---|-----|---|
| 3 | ne | п | _ | пе | Ξ |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0