NSN 5306-00-508-6230

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-6230 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.601 inches and 0.651 inches **Fastener Length:** Between 2.111 inches and 2.141 inches **Head Style:** Dished hexagon **Head Height:** Between 0.312 inches and 0.327 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Grip Diameter:** Between 0.6235 inches and 0.6240 inches **Shank Unthreaded Hole Diameter:** 0.141 inches and 0.151 inches first hole **Thread Diameter:** 0.625 inches **Grip Length:** Between 1.490 inches and 1.510 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.894 inches and 1.944 inches first hole **Product Name:** Navy special project Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6410 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5306-00-508-6230

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0