## NSN 5306-00-508-6339

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-6339

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 0.433 inches and 0.463 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Shank Unthreaded Hole Diameter:
0.070 inches and 0.080 inches first hole
Thread Diameter:
0.190 inches
Grip Length:
Between 0.115 inches and 0.135 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.259 inches and 0.309 inches first hole
Product Name:
Navy special project
Material:
Titanium alloy
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6403 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-00-508-6339

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0