NSN 5306-00-508-6480

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-6480

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.503 inches and 0.553 inches Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3 Hole Type:
Thread Direction: Right-hand Thread Length: Between 0.503 inches and 0.553 inches Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Right-hand Thread Length: Between 0.503 inches and 0.553 inches Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Thread Length: Between 0.503 inches and 0.553 inches Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Between 0.503 inches and 0.553 inches Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Fastener Length: Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Between 1.325 inches and 1.355 inches Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity: 3
Head Style: Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Dished hexagon Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Head Height: Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Between 0.219 inches and 0.234 inches Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Width Between Flats: Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Between 0.679 inches and 0.690 inches Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Hole Diameter: 0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
0.075 inches Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Grip Diameter: Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Between 0.4365 inches and 0.4370 inches Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Thread Diameter: 0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
0.438 inches Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Grip Length: Between 0.802 inches and 0.822 inches Hole Quantity:
Between 0.802 inches and 0.822 inches Hole Quantity:
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Hexagon corners Surface Finish:
-
Surface Finish:
Surface Finish: 32.0 microinches threads
Surface Finish: 32.0 microinches threads Material:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response

80205-nas6307 professional/industrial association standard

NSN 5306-00-508-6480

Shear Bolt - Page 2 of 2



_					
٠.	h	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0