NSN 5306-00-508-7044

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-508-7044 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.254 inches and 1.274 inches **Fastener Length:** 3.389 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.808 inches Width Between Flats: Between 0.928 inches and 0.940 inches **Extended Washer Diameter:** Between 1.428 inches and 1.438 inches **Extended Washer Thickness:** 0.198 inches **Grip Diameter:** Between 0.8730 inches and 0.8740 inches **End Application:** Aircraft, (ac-130h, mc-130h, ec-130e, hc-130); aircraft, hercules c-**Thread Diameter:** 0.875 inches **Grip Length:** Between 2.115 inches and 2.135 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 43.0 rockwell c Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification all treatment responses **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-00-508-7044

Shear Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0