NSN 5306-00-510-5338

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-510-5338 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.589 inches and 0.609 inches **Fastener Length:** 1.224 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.348 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** 0.082 inches **Hole Diameter:** 0.055 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi):

180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole Material: Steel **Surface Treatment:** Cadmium and chromate

NSN 5306-00-510-5338

Shear Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-416, type 2 cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0