

View Online at <https://aerobasegroup.com/nsn/5306-00-510-6694>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.499 inches and 0.580 inches

**Fastener Length:**

Between 2.403 inches and 2.433 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.247 inches and 0.267 inches

**Width Between Flats:**

Between 0.678 inches and 0.689 inches

**Shoulder Diameter:**

0.436 inches first shoulder and 0.437 inches first shoulder

**Shoulder Length:**

1.811 inches first shoulder and 1.821 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**Thread Diameter:**

0.375 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.196 inches first hole and 2.246 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0