NSN 5306-00-512-6422

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-512-6422

view Offine at https://aerobasegroup.com
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.475 inches and 0.525 inches
Fastener Length:
Between 1.485 inches and 1.515 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.244 inches and 0.264 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.465 inches and 0.475 inches
Extended Washer Thickness:
Between 0.032 inches and 0.052 inches
Hole Diameter:
Between 0.150 inches and 0.190 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.990 inches and 1.010 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
32.0 microinches grip
Product Name:
Navy special project
Material:
Nickel alloy k-500

NSN 5306-00-512-6422

Machine Bolt - Page 2 of 2



	Materia	al Sp	ecific	ation:
--	---------	-------	--------	--------

Ams 5662 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0