Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-513-4703

Thread	Class:

3a

Thread Direction:

**Right-hand** 

### Thread Length:

0.630 inches

#### Fastener Length:

3.580 inches

#### Head Style:

Hexagon

Head Height:

0.220 inches

#### Width Between Flats:

0.560 inches

Shank Unthreaded Hole Diameter:

0.108 inches first hole

## Thread Diameter:

0.375 inches

#### \_ . . . .

Grip Length:

# 2.950 inches

**Features Provided:** 

Finished head

#### Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

155000 pounds per square inch

#### Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

## Distance From Head Largest Bearing Surface To Shank Hole Center:

3.375 inches first hole

Material:

Steel comp 4140

## Material Specification:

Mil-s-562 military specification single material response

#### Surface Treatment:

Chromium

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5306-00-513-4703

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-562 spec.

