NSN 5306-00-514-9380

Machine Bolt - Page 1 of 2

Between 0.615 inches and 0.625 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-00-514-9380

| Fastener Length: |
|---|
| Between 0.615 inches and 0.625 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.365 inches and 0.385 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Extended Washer Diameter: |
| Between 0.428 inches and 0.448 inches |
| Extended Washer Thickness: |
| Between 0.070 inches and 0.080 inches |
| Hole Diameter: |
| 0.065 inches |
| Thread Diameter: |
| 0.312 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Surface Finish: |
| 63.0 microinches bearing surface of head |
| Material: |
| Steel comp 8740 |
| Material Specification: |
| Ams 6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| |
| |

NSN 5306-00-514-9380

Machine Bolt - Page 2 of 2



| Surface Treatment Spec | ific | ation: |
|------------------------|------|--------|
|------------------------|------|--------|

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0