## NSN 5306-00-515-7060

Ring Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-515-7060 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.499 inches and 0.578 inches **Eye Inside Diameter:** Between 0.313 inches and 0.316 inches **Shoulder Thickness:** 0.094 inches **Shank Length:** Between 2.203 inches and 2.250 inches **Eye Stock Thickness:** Between 0.183 inches and 0.193 inches **Shoulder Diameter:** 0.688 inches **Shank Unthreaded Hole Diameter:** 0.066 inches first hole and 0.086 inches first hole **Ring Stock Diameter:** 0.250 inches **Ring Inside Diameter:** 1.375 inches **Overall Length:** 3.204 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 45 **Distance From Center Of Eye To Shank End:** 2.939 inches **Eye Outside Width:** 0.688 inches Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Style Designator:** Round, closed w/shoulder

Unf

**Thread Series Designator:** 

## NSN 5306-00-515-7060

Ring Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0