Externally Relieved Body Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-515-9015



Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.370 inches and 0.430 inches
Fastener Length:
Between 0.918 inches and 0.928 inches
Head Style:
Hexagon
Head Height:
0.203 inches
Width Between Flats:
0.500 inches
Hole Diameter:
0.062 inches
First Diameter From Head:
Between 0.307 inches and 0.312 inches
Second Diameter From Head:
Between 0.229 inches and 0.233 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.120 inches and 0.160 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
Between 0.498 inches and 0.548 inches
Thread Diameter:
0.312 inches
Hole Quantity:
2
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
24
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Hole Configuration Style:
Hexagon flats
Externally Relieved Body Diameter Quantity:
2
Product Name:
Navy special project
Material:
Steel comp 8740

Externally Relieved Body Bolt - Page 2 of 2



Material Specification:

Ams 6322 assn standard single material response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0