NSN 5306-00-516-5651

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-516-5651 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.364 inches and 0.441 inches **Fastener Length:** Between 2.009 inches and 2.056 inches **Head Style:** Double hexagon **Head Height:** Between 0.200 inches and 0.220 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches first hole and 0.111 inches first hole **End Application:** Aircraft phantom f-4 **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.615 inches and 1.635 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.884 inches first hole and 1.941 inches first hole Material: Steel **Material Specification:** 23-105 fscm 76301 mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Mac ps13145 fscm 76301 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a
Unit Of Measure:

NSN 5306-00-516-5651

Close Tolerance Bolt - Page 2 of 2



em			

No

Fiig:

A003b0