

View Online at <https://aerobasegroup.com/nsn/5306-00-518-5677>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.656 inches and 1.735 inches

Fastener Length:

Between 3.047 inches and 3.094 inches

Head Style:

Hexagon

Head Height:

Between 0.640 inches and 0.672 inches

Width Between Flats:

Between 1.802 inches and 1.815 inches

End Application:

Spec item

Thread Diameter:

1.250 inches

Grip Length:

Between 1.359 inches and 1.391 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.