

View Online at <https://aerobasegroup.com/nsn/5306-00-518-5677>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.656 inches and 1.735 inches

**Fastener Length:**

Between 3.047 inches and 3.094 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.640 inches and 0.672 inches

**Width Between Flats:**

Between 1.802 inches and 1.815 inches

**End Application:**

Spec item

**Thread Diameter:**

1.250 inches

**Grip Length:**

Between 1.359 inches and 1.391 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Material:**

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 4130

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6758 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.