## NSN 5306-00-518-6197

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-518-6197 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.633 inches and 0.693 inches **Fastener Length:** Between 2.460 inches and 2.490 inches **Head Style:** Hexagon **Head Height:** Between 0.203 inches and 0.235 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.797 inches and 1.827 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a Unit Of Measure: --

## NSN 5306-00-518-6197

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.