## NSN 5306-00-522-2478

N/a

Externally Relieved Body Bolt - Page 1 of 2



, , , ,
View Online at https://aerobasegroup.com/nsn/5306-00-522-2478
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.562 inches
Fastener Length:
0.875 inches
Head Style:
Hexagon
Head Height:
0.234 inches
Width Between Flats:
0.500 inches
Shank Unthreaded Hole Diameter:
0.078 inches first hole and 0.083 inches first hole
First Diameter From Head:
0.266 inches
Second Diameter From Head:
Between 0.296 inches and 0.311 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.078 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
0.234 inches
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
0.781 inches first hole
Externally Relieved Body Diameter Quantity:
1
Material:
Steel
Material Specification:
Qq-s-631 federal specification single material response or astm a108 assn standard single material response or qq-s-637 federal
specification single material response
Surface Treatment:
Phosphate
Thread Series Designator:
Unf
Shelf Life:

## NSN 5306-00-522-2478

Externally Relieved Body Bolt - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0