## NSN 5306-00-522-3990

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-522-3990 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.188 inches **Head Style:** Hexagon **Head Height:** 0.188 inches Width Between Flats: 0.687 inches **Shank Unthreaded Hole Diameter:** 0.078 inches first hole First Diameter From Head: 0.375 inches **Second Diameter From Head:** Between 0.310 inches and 0.311 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.687 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.188 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Minimum Yield Strength: 60000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.062 inches first hole **Externally Relieved Body Diameter Quantity:** 2 Material: Steel **Material Specification:** Mil-s-11415, cl c2 military specification single material response **Surface Treatment:** Cadmium **Thread Series Designator:** 

Unf

## NSN 5306-00-522-3990

Externally Relieved Body Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-11415 spec.

Shelf Life: