

View Online at <https://aerobasegroup.com/nsn/5306-00-522-3990>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.500 inches

**Fastener Length:**

1.188 inches

**Head Style:**

Hexagon

**Head Height:**

0.188 inches

**Width Between Flats:**

0.687 inches

**Shank Unthreaded Hole Diameter:**

0.078 inches first hole

**First Diameter From Head:**

0.375 inches

**Second Diameter From Head:**

Between 0.310 inches and 0.311 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.687 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.188 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Minimum Yield Strength:**

60000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.062 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel

**Material Specification:**

Mil-s-11415, cl c2 military specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-11415 spec.