## NSN 5306-00-522-9939

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-522-9939

3aThread Direction:Right-handThread Length:0.583 inchesFastener Length:Between 1.756 inches and 1.786 inchesHead Style:Double hexagon w/holeHead Height:Between 0.312 inches and 0.332 inchesWidth Between Flats:0.491 inchesBetween 0.639 inches and 0.649 inchesExtended Washer Diameter:Between 0.081 inches and 0.101 inchesHole Diameter:Between 0.3735 inches and 0.3745 inches
Right-handThread Length:0.583 inchesFastener Length:Between 1.756 inches and 1.786 inchesHead Style:Double hexagon w/holeHead Height:Between 0.312 inches and 0.332 inchesWidth Between Flats:0.491 inchesExtended Washer Diameter:Between 0.639 inches and 0.649 inchesExtended Washer Thickness:Between 0.081 inches and 0.101 inchesHole Diameter:Between 0.050 inches and 0.060 inchesGrip Diameter:Between 0.3735 inches and 0.3745 inches
Thread Length:0.583 inchesFastener Length:Between 1.756 inches and 1.786 inchesHead Style:Double hexagon w/holeHead Height:Between 0.312 inches and 0.332 inchesWidth Between Flats:0.491 inchesExtended Washer Diameter:Between 0.639 inches and 0.649 inchesExtended Washer Thickness:Between 0.081 inches and 0.101 inchesHole Diameter:Between 0.050 inches and 0.060 inchesGrip Diameter:Between 0.3735 inches and 0.3745 inches
0.583 inches Fastener Length: Between 1.756 inches and 1.786 inches Head Style: Double hexagon w/hole Head Height: Between 0.312 inches and 0.332 inches Width Between Flats: 0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Fastener Length:Between 1.756 inches and 1.786 inchesHead Style:Double hexagon w/holeHead Height:Between 0.312 inches and 0.332 inchesWidth Between Flats:0.491 inchesExtended Washer Diameter:Between 0.639 inches and 0.649 inchesExtended Washer Thickness:Between 0.081 inches and 0.101 inchesHole Diameter:Between 0.050 inches and 0.060 inchesGrip Diameter:Between 0.3735 inches and 0.3745 inches
Between 1.756 inches and 1.786 inches Head Style: Double hexagon w/hole Head Height: Between 0.312 inches and 0.332 inches Width Between Flats: 0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Head Style:Double hexagon w/holeHead Height:Between 0.312 inches and 0.332 inchesWidth Between Flats:0.491 inchesExtended Washer Diameter:Between 0.639 inches and 0.649 inchesExtended Washer Thickness:Between 0.081 inches and 0.101 inchesHole Diameter:Between 0.050 inches and 0.060 inchesGrip Diameter:Between 0.3735 inches and 0.3745 inches
Double hexagon w/hole Head Height: Between 0.312 inches and 0.332 inches Width Between Flats: 0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Head Height: Between 0.312 inches and 0.332 inches Width Between Flats: 0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Between 0.312 inches and 0.332 inches Width Between Flats: 0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
<ul> <li>Width Between Flats:</li> <li>0.491 inches</li> <li>Extended Washer Diameter:</li> <li>Between 0.639 inches and 0.649 inches</li> <li>Extended Washer Thickness:</li> <li>Between 0.081 inches and 0.101 inches</li> <li>Hole Diameter:</li> <li>Between 0.050 inches and 0.060 inches</li> <li>Grip Diameter:</li> <li>Between 0.3735 inches and 0.3745 inches</li> </ul>
0.491 inches Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Extended Washer Diameter: Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Between 0.639 inches and 0.649 inches Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Extended Washer Thickness: Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Between 0.081 inches and 0.101 inches Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Hole Diameter: Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Between 0.050 inches and 0.060 inches Grip Diameter: Between 0.3735 inches and 0.3745 inches
Grip Diameter: Between 0.3735 inches and 0.3745 inches
Between 0.3735 inches and 0.3745 inches
Thursd Discussion
Thread Diameter:
0.375 inches
Grip Length:
1.188 inches
Hole Quantity:
4
Ноје Туре:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response

## NSN 5306-00-522-9939

Close Tolerance Bolt - Page 2 of 2



Surface Treatment: Cadmium and chromate Surface Treatment Specification: Mil-c-8837 type 2 cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A003b0 Mil-std (military Standard): Mil-c-8837 spec.