

View Online at <https://aerobasegroup.com/nsn/5306-00-526-4076>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.455 inches and 0.595 inches

Fastener Length:

Between 1.005 inches and 1.025 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.293 inches and 0.313 inches

Width Between Flats:

0.312 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

0.060 inches

First Diameter From Head:

Between 0.250 inches and 0.252 inches

Second Diameter From Head:

Between 0.185 inches and 0.195 inches

Third Diameter From Head:

Between 0.250 inches and 0.252 inches

Fourth Diameter From Head:

Between 0.165 inches and 0.175 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.205 inches and 0.225 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.310 inches and 0.320 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.360 inches and 0.370 inches

Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:

Between 0.430 inches and 0.550 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

175000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 44.0 rockwell c

Minimum Yield Strength:

115000 pounds per square inch

Externally Relieved Body Diameter Quantity:

4

Material:

Nickel alloy

Material Specification:

Ams 5708 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0