

View Online at <https://aerobasegroup.com/nsn/5306-00-528-5032>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.345 inches and 0.395 inches

**Fastener Length:**

Between 2.355 inches and 2.385 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.125 inches and 0.140 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 1.990 inches and 2.010 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.175 inches first hole and 2.225 inches first hole

**Surface Finish:**

32.0 microinches threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6304 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0