NSN 5306-00-528-5521



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-528-5521 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 1.989 inches and 2.019 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.678 inches and 1.698 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.861 inches first hole and 1.911 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas654 professional/industrial association standard

N/a

Shelf Life:

Unit Of Measure:

--

NSN 5306-00-528-5521

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0