NSN 5306-00-529-3210

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-529-3210 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.125 inches **Fastener Length:** 3.062 inches **Head Style:** Hexagon **Head Height:** 0.312 inches Width Between Flats: 1.500 inches **Shoulder Diameter:** 0.997 inches first shoulder **Shoulder Length:** 1.695 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.156 inches first hole **Thread Diameter:** 0.750 inches **Features Provided:** Casehardened Thready Qty Per Inch (tpi): 16 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.781 inches first hole **Shoulder Shape:** Round first shoulder **Special Features:** Gground body finish on largest shoulder; thd portion case drawn; undercut 0.978 in. Plus 0.010 diameter by 0.062 in. Lg located under head; undercut 23/32 in. Diameter by 0.062 in. Lg located at end of shoulder Material: Steel comp 1212 **Material Specification:** Qq-s-633 federal specification single material response **Thread Series Designator:**

Unit Of Measure:

Shelf Life:

Unf

N/a

NSN 5306-00-529-3210

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0