NSN 5306-00-529-9235

Machine Bolt - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5306-00-529-9235



3a **Thread Direction: Right-hand Thread Length:** Between 0.843 inches and 0.893 inches Fastener Length: Between 5.103 inches and 5.133 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.608 inches and 0.628 inches Width Between Flats: Between 0.679 inches and 0.690 inches **Extended Washer Diameter:** Between 1.040 inches and 1.050 inches **Extended Washer Thickness:** 0.327 inches **Thread Diameter:** 0.625 inches Grip Length: Between 4.240 inches and 4.260 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 220000 pounds per square inch Surface Finish: 32.0 microinches grip Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response Surface Treatment: Cadmium or cadmium **Surface Treatment Specification:** Nas 672 assn standard 1st treatment response or mil-c-8837, type 2, cl 3 military specification 2nd treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5306-00-529-9235

Machine Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.

