

View Online at <https://aerobasegroup.com/nsn/5306-00-529-9981>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.374 inches and 0.441 inches

**Fastener Length:**

Between 2.384 inches and 2.431 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.200 inches and 0.220 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.990 inches and 2.010 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.259 inches first hole and 2.316 inches first hole

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mac ps13145, mcdonnell douglas corporation mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

08524-b-17028 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0