

View Online at <https://aerobasegroup.com/nsn/5306-00-530-0283>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.622 inches and 0.642 inches

**Shank Length:**

1.132 inches

**Eye Stock Diameter:**

0.562 inches

**Shoulder Diameter:**

Between 0.368 inches and 0.373 inches

**Shoulder Length:**

Between 0.490 inches and 0.510 inches

**Ring Stock Diameter:**

Between 0.250 inches and 0.270 inches

**Thread Diameter:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 2 class 3 federal specification 1st treatment response or qq-z-325 type 2 class 3 federal specification 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1251 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.