

View Online at <https://aerobasegroup.com/nsn/5306-00-530-0283>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.622 inches and 0.642 inches

Shank Length:

1.132 inches

Eye Stock Diameter:

0.562 inches

Shoulder Diameter:

Between 0.368 inches and 0.373 inches

Shoulder Length:

Between 0.490 inches and 0.510 inches

Ring Stock Diameter:

Between 0.250 inches and 0.270 inches

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 2 class 3 federal specification 1st treatment response or qq-z-325 type 2 class 3 federal specification 2nd treatment response

Style Designator:

Swivel

Thread Series Designator:

Unjf

Specification Data:

80205-nas1251 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.