

View Online at <https://aerobasegroup.com/nsn/5306-00-530-0327>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.332 inches and 0.399 inches

**Fastener Length:**

Between 2.780 inches and 2.827 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.140 inches and 0.145 inches

**Width Between Flats:**

Between 0.492 inches and 0.502 inches

**Grip Diameter:**

Between 0.3108 inches and 0.3117 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 2.428 inches and 2.448 inches

**Thread Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.654 inches first hole and 2.686 inches first hole

**Material:**

Steel

**Material Specification:**

Sps-m-107, standard pressed steel co mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Mil-c-8837 type 1 class 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-8837 spec.