

View Online at <https://aerobasegroup.com/nsn/5306-00-530-9854>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.866 inches and 0.946 inches

**Fastener Length:**

Between 1.428 inches and 1.448 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.490 inches and 0.510 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**Hole Diameter:**

0.065 inches

**First Diameter From Head:**

Between 0.276 inches and 0.286 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.502 inches and 0.562 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Nonstandard Thread Pitch Diameter:**

+0.3023/+0.3095 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0