

View Online at <https://aerobasegroup.com/nsn/5306-00-530-9854>

Thread Direction:

Right-hand

Thread Length:

Between 0.866 inches and 0.946 inches

Fastener Length:

Between 1.428 inches and 1.448 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.065 inches

First Diameter From Head:

Between 0.276 inches and 0.286 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.502 inches and 0.562 inches

Thread Diameter:

0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.3023/+0.3095 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0