NSN 5306-00-531-1012



Machine Bolt - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5306-00-531-1012 **Thread Class:** 2a **Thread Direction:** Right-hand **Thread Length:** 0.500 inches **Fastener Length:** 1.750 inches **Head Style:** Hexagon **Head Height:** 0.120 inches Width Between Flats: 0.380 inches **Thread Diameter:** 0.190 inches **Grip Length:** 1.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Material: Steel comp 1211 or steel comp 1212 or steel comp 1213 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1020 or steel comp 1022 or steel comp 1025 **Material Specification:** Qq-s-637 federal specification 1st material response or qq-s-637 federal specification 2nd material response or qq-s-637 federal

specification 3rd material response or qq-s-637 federal specification 4th material response or qq-b-637 federal specification 5th material response or qq-b-637 federal specification all material responses or astm a108 assn standard 6th material response or astm a108 assn standard 7th material response or astm a108 assn standard 8th material response or astm a108 assn standard 9th material response or astm a108 assn standard 10th material response or astm a108 assn standard 11th material response

Surface Treatment:

Phosphate manganese or phosphate zinc

Surface Treatment Specification:

Mil-s-16232 military specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: