

View Online at <https://aerobasegroup.com/nsn/5306-00-533-8774>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.333 inches and 0.400 inches

Fastener Length:

Between 1.593 inches and 1.640 inches

Head Style:

Double hexagon

Head Height:

Between 0.140 inches and 0.145 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.466 inches first hole and 1.498 inches first hole

Material:

Steel

Material Specification:

Sps-m-107, standard pressed steel co mfr ref single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0