

View Online at <https://aerobasegroup.com/nsn/5306-00-534-3855>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.516 inches

**Fastener Length:**

Between 0.678 inches and 0.698 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.365 inches and 0.385 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

Between 0.070 inches and 0.080 inches

**First Diameter From Head:**

Between 0.311 inches and 0.312 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.100 inches and 0.110 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

Between 0.100 inches and 0.110 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0