## NSN 5306-00-534-3855

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-534-3855 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.516 inches **Fastener Length:** Between 0.678 inches and 0.698 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.311 inches and 0.312 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.100 inches and 0.110 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: Between 0.100 inches and 0.110 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8740 **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response

Unf

**Thread Series Designator:** 

## NSN 5306-00-534-3855

Externally Relieved Body Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0