## NSN 5306-00-538-6899

Machine Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-00-538-6899



3a **Thread Direction: Right-hand Thread Length:** Between 0.740 inches and 0.820 inches Fastener Length: Between 1.428 inches and 1.448 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.302 inches and 0.322 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.060 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.628 inches and 0.688 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c **Minimum Yield Strength:** 85000 pounds per square inch Hole Configuration Style: Double hexagon longitudinal hole Surface Finish:

32.0 microinches threads

## NSN 5306-00-538-6899

Machine Bolt - Page 2 of 2

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

