## NSN 5306-00-541-9040



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-541-9040 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.883 inches and 0.933 inches **Fastener Length:** Between 11.893 inches and 11.923 inches **Head Style:** Dished hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Shank Unthreaded Hole Diameter:** 0.106 inches and 0.116 inches first hole **Thread Diameter:** 0.375 inches **Grip Length:** Between 10.990 inches and 11.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 11.700 inches and 11.750 inches first hole **Product Name:** Navy special project Material: Titanium alloy

**Material Specification:** 

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

**Specification Data:** 

80205-nas6406 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5306-00-541-9040

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0