## NSN 5306-00-543-5582

Machine Bolt - Page 1 of 1

A003b0



View Online at https://aerobasegroup.com/nsn/5306-00-543-5582

Inread Direction: Right-hand Thread Length: 1.250 inches Fastener Length: Between 3.437 inches and 3.562 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.756 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready Oty Per Inch (tpi): 13 Material: Q-q-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-v-423 federal specification 3rd material response or qq-v-423 federal specification fish material response or qq-v-423 federal specific	
Right-hand Thread Length: 1,250 inches Fastener Length: Between 3,437 inches and 3,562 inches Head Style: Hexagon Head Height: Between 0,302 inches and 0,323 inches Width Between Flats: Between 0,302 inches and 0,323 inches Width Between Flats: Between 0,725 inches and 0,750 inches Thread Diameter: 0,500 inches Grip Length: 2,250 inches Fastures Provided: Finished head Thread Diameter: 13 Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-5-763 lederal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 6th material response or qq-w-423 fede	Thread Class:
Right-hand Thread Length: 1.250 inches Fastener Length: Between 3.457 inches and 3.562 inches Head Style: Hexagon Head Height: Between 0.725 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Grip Length: 2.250 inches Fastures Provided: Finished head Thready Oty Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: 0.430-783 federal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specifi	
Tread Length:  1.250 inches  Fastener Length:  Between 3.437 inches and 3.562 inches  Head Style: Hexagon  Head Height:  Between 0.302 inches and 0.323 inches  Width Between 7.25 inches and 0.750 inches  Thread Diameter:  0.500 inches  Thread Diameter: 0.500 inches  Forip Length: 2.250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi):  13  Material:  Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material specification 1st material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 6th material response or qq-w-42	
1.250 inches Fastener Length: Between 3.437 inches and 3.562 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Wildth Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready ty Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal spec	
Fastener Length: Between 3.437 inches and 3.562 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready Day Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification 1st material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 6th material response or qq-w-423 f	-
Between 3.437 inches and 3.562 inches  Head Style: Hexagon  Head Helght: Between 0.302 inches and 0.323 inches  Width Between Flats: Between 0.725 inches and 0.750 inches  Thread Diameter: 0.500 inches  Grip Length: 2.500 inches  Fatures Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material	
Head Style: Hexagon  Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Grip Length: 1.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or ag-w-423 federal specification 5th material response or aq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-	Fastener Length:
Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material r	Between 3.437 inches and 3.562 inches
Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.725 inches and 0.750 inches Thread Dlameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response Surface Treatment Specification: Qq-g-35 Geteral specification single treatment response Thready Series Designator: Unc Shelf Life: N/a	Head Style:
Between 0.302 inches and 0.323 inches  Width Between Flats:  Between 0.725 inches and 0.750 inches  Thread Diameter: 0.500 inches  Grip Length: 2.250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification: Q-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Thread Series Designator:  Unc  Shelf Life:  N/a	Hexagon
Width Between Flats: Between 0.725 inches and 0.750 inches Thread Diameter: 0.500 inches Grip Length: 2.250 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 13 Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316 Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Head Height:
Between 0.725 inches and 0.750 inches  Thread Diameter: 0.500 inches  Grip Length: 2.250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a	Between 0.302 inches and 0.323 inches
Thread Diameter:  0.500 inches  Grip Length: 2.250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 6th material r	Width Between Flats:
0.500 inches  Grip Length: 2.250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification: Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-w-42	Between 0.725 inches and 0.750 inches
Grip Length:  2.250 inches  Features Provided: Finished head  Thready Otty Per Inch (tpi):  13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a	Thread Diameter:
2,250 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment: Passivate  Surface Treatment Specification: Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc  Shelf Life: N/a	0.500 inches
Features Provided: Finished head  Thready Qty Per Inch (tpi):  13  Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment: Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life: N/a	Grip Length:
Finished head  Thready Qty Per Inch (tpi):  13  Material:  Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	2.250 inches
Thready Qty Per Inch (tpi):  13  Material:  Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Features Provided:
Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Finished head
Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Thready Qty Per Inch (tpi):
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316  Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	13
Material Specification:  Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Material:
Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard 2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 310 or steel comp 316
2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 5th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Material Specification:
qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	Qq-s-763 federal specification 1st material response or qq-w-423 federal specification 1st material response or astm a582 assn standard
specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material response  Surface Treatment:  Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	2nd material response or qq-s-763 federal specification 3rd material response or qq-w-423 federal specification 3rd material response or
response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or qq-w-423 federal
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	specification 5th material response or qq-s-763 federal specification 6th material response or qq-w-423 federal specification 6th material
Passivate  Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unc  Shelf Life:  N/a	response
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment:
Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc Shelf Life: N/a	Passivate
Qq-p-35 federal specification single treatment response  Thread Series Designator: Unc Shelf Life: N/a	Surface Treatment Specification:
Thread Series Designator: Unc Shelf Life: N/a	
Unc Shelf Life: N/a	
Shelf Life: N/a	
N/a	
Demilitarization:	Demilitarization:
No No	
	Fiig: