## NSN 5306-00-544-2955



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-544-2955 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.834 inches and 0.884 inches **Fastener Length:** Between 2.719 inches and 2.749 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.434 inches and 0.454 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 1.865 inches and 1.885 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c **Product Name:** Navy special project Material: Steel comp h11

**Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-00-544-2955

Shear Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0