

View Online at <https://aerobasegroup.com/nsn/5306-00-545-3282>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.550 inches

Fastener Length:

3.110 inches

Head Style:

Round w/wrench flats chamfered

Head Diameter:

1.000 inches

Head Height:

0.250 inches

Width Between Flats:

Between 0.740 inches and 0.752 inches

Shank Unthreaded Hole Diameter:

0.068 inches first hole and 0.073 inches first hole

First Diameter From Head:

Between 0.308 inches and 0.318 inches

Second Diameter From Head:

Between 0.495 inches and 0.499 inches

Third Diameter From Head:

Between 0.308 inches and 0.318 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.120 inches and 0.130 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.820 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.950 inches

Thread Diameter:

0.375 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.230 inches first hole

Externally Relieved Body Diameter Quantity:

3

Material:

Steel

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0