

View Online at <https://aerobasegroup.com/nsn/5306-00-550-0248>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.063 inches and 1.141 inches

Fastener Length:

Between 4.891 inches and 4.938 inches

Head Style:

Hexagon

Head Height:

Between 0.390 inches and 0.422 inches

Width Between Flats:

Between 1.053 inches and 1.066 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.151 inches first hole

Thread Diameter:

0.750 inches

Grip Length:

Between 3.797 inches and 3.828 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

4.672 inches first hole and 4.703 inches first hole

Material:

Steel comp 431

Material Specification:

Mil-s-18732 military specification single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.