

View Online at <https://aerobasegroup.com/nsn/5306-00-550-1176>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.375 inches

**Fastener Length:**

7.125 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.515 inches and 0.547 inches

**Width Between Flats:**

Between 1.428 inches and 1.441 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole

**Thread Diameter:**

1.000 inches

**Grip Length:**

5.750 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

14

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

6.844 inches first hole

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-b-6812 military specification all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-b-6812 spec.