NSN 5306-00-550-3744

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-550-3744

~	
-	
-	hread Direction:
	Right-hand
	Thread Length:
	.469 inches
	astener Length:
-	.531 inches
	lead Style:
	lexagon
Н	lead Height:
B	Between 0.140 inches and 0.172 inches
	Vidth Between Flats:
B	Between 0.428 inches and 0.440 inches
Н	lole Diameter:
0	.046 inches
S	hank Unthreaded Hole Diameter:
0	.076 inches first hole
Т	hread Diameter:
0	.250 inches
G	Grip Length:
0	.062 inches
Η	lole Quantity:
1	
Н	юе Туре:
D	Drilled
F	eatures Provided:
F	inished head
т	hready Qty Per Inch (tpi):
2	8
N	lin. Tensile Strength (psi):
1	25000 pounds per square inch
Н	lardness Rating:
2	6.0 rockwell c and 32.0 rockwell c
Н	lole Configuration Style:
Н	lexagon longitudinal hole
D	Distance From Head Largest Bearing Surface To Shank Hole Center:
0	.374 inches first hole
N	laterial:
s	stainless steel
	laterial Specification:

NSN 5306-00-550-3744

Machine Bolt - Page 2 of 2

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

