NSN 5306-00-550-4973

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-550-4973

Right-hand Thread Length: Between 0.544 inches and 0.615 inches Fastener Length: Between 0.615 inches and 0.635 inches Head Style: Double hexagon w/hole Head Height: Between 0.615 inches and 0.635 inches Width Between Flats: Between 0.309 inches and 0.314 inches Extended Washer Diameter: Between 0.428 inches and 0.476 inches Extended Washer Thickness: Between 0.600 inches and 0.070 inches Hole Diameter: 0.060 inches 0.060 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: 4.02.213/40.2238 inches Horelougit 28 Hould Configuration Style: 0.0.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material Steel comp 601 Material Steel comp 601 Material By	Thread Direction:
Between 0.614 inches and 0.615 inchesFastener Length:Between 0.615 inches and 0.635 inchesHead Style:Double hexagon w/holeHead Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inches10.600 inchesHole Quantity:4Hole Type:DrilledFastended Thread Pitch Diameter:0.2213/+0.2238 inchesFinshed headNonstandard Thread Pitch Diameter:0.2213/+0.2238 inchesHardenss Rating:0.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material:Kiekel and cadmium	Right-hand
Fastener Length:Between 0.615 inches and 0.635 inchesHead Style:Double hexagon w/holeHead Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inches10.060 inchesHole Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Thread Length:
Between 0.615 inches and 0.635 inchesHead Style:Double hexagon w/holeHead Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.600 inches and 0.070 inchesHole Diameter:0.060 inches10.060 inchesHole Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Plich Diameter:0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Between 0.544 inches and 0.615 inches
Head Style:Double hexagon w/holeHead Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inchesThread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:4.0.213/+0.2238 inchesThready Qty Per Inch (tpi):28Hole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Fastener Length:
Double hexagon w/holeHead Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inchesThread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:0.0.0 rockwell c and 38.0 rockwell cHeir Configuration Style:Double hexagon longitudinal holeMaterialSteel comp 601Material Specification:Arns 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Between 0.615 inches and 0.635 inches
Head Height:Between 0.615 inches and 0.635 inchesWidth Between Flats:Between 0.309 inches and 0.314 inchesExtended Washer Diameter:Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inchesThread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:4.0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterialSteel comp 601Material Specification:Arns 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Head Style:
Between 0.615 inches and 0.635 inches Width Between Flats: Between 0.309 inches and 0.314 inches Extended Washer Diameter: Between 0.428 inches and 0.448 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Arns 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Double hexagon w/hole
Width Between Flats: Between 0.309 inches and 0.314 inches Extended Washer Diameter: Between 0.428 inches and 0.448 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: 4.0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Head Height:
Between 0.309 inches and 0.314 inches Extended Washer Diameter: Between 0.428 inches and 0.448 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Between 0.615 inches and 0.635 inches
Extended Washer Diameter: Between 0.428 inches and 0.448 inches Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Width Between Flats:
Between 0.428 inches and 0.448 inchesExtended Washer Thickness:Between 0.060 inches and 0.070 inchesHole Diameter:0.060 inchesThread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:4.0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Between 0.309 inches and 0.314 inches
Extended Washer Thickness: Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Arms 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Extended Washer Diameter:
Between 0.060 inches and 0.070 inches Hole Diameter: 0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Between 0.428 inches and 0.448 inches
Hole Diameter:0.060 inchesThread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Extended Washer Thickness:
0.060 inches Thread Diameter: 0.250 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Between 0.060 inches and 0.070 inches
Thread Diameter:0.250 inchesHole Quantity:4Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Hole Diameter:
0.250 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	0.060 inches
Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Thread Diameter:
4 Hole Type: Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	0.250 inches
Hole Type:DrilledFeatures Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Hole Quantity:
Drilled Features Provided: Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	4
Features Provided:Finished headNonstandard Thread Pitch Diameter:+0.2213/+0.2238 inchesThready Qty Per Inch (tpi):28Hardness Rating:30.0 rockwell c and 38.0 rockwell cHole Configuration Style:Double hexagon longitudinal holeMaterial:Steel comp 601Material Specification:Ams 6304 assn standard single material responseSurface Treatment:Nickel and cadmium	Hole Type:
Finished head Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Drilled
Nonstandard Thread Pitch Diameter: +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Features Provided:
 +0.2213/+0.2238 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium 	Finished head
Thready Qty Per Inch (tpi): 28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Nonstandard Thread Pitch Diameter:
28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	+0.2213/+0.2238 inches
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Thready Qty Per Inch (tpi):
30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	28
Hole Configuration Style: Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Hardness Rating:
Double hexagon longitudinal hole Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	30.0 rockwell c and 38.0 rockwell c
Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Hole Configuration Style:
Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Double hexagon longitudinal hole
Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Material:
Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium	Steel comp 601
Surface Treatment: Nickel and cadmium	Material Specification:
Nickel and cadmium	Ams 6304 assn standard single material response
	Surface Treatment:
Surface Treatment Specification:	Nickel and cadmium
	Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

NSN 5306-00-550-4973

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

