NSN 5306-00-551-7008

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-551-7008 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.810 inches **Fastener Length:** 1.125 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.315 inches and 0.375 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a

NSN 5306-00-551-7008Machine Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A003b0