NSN 5306-00-558-2763

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-558-2763

3a Firead Direction: Right-hand Tread Length: 0.537 inches Fastern Length: Between 1.673 inches and 1.703 inches Head Style: Bevel-conical Head Diameter: 0.532 inches Head Height: 0.535 inches Head Height: 0.535 inches Head Raigen: 0.555 inches Head Raigen: 0.555 inches Head Paineter: 0.555 inches Head Paineter: 0.555 inches Head Style: Paineter: 0.312 inches Hexagon Thread Diameter: 0.312 inches Hole Nameter: 0.312 inches Hole Quantity: 4 Hole Quantity: 1 Hole Quantity: 24 Hole Type: 1 10000 pounds per square inch 10000 pounds per square inch
Right-hand Tread Length: 0.537 inches Fastener Length: Between 1.673 inches and 1.703 inches Head Style: Bevel-conical Head Oinmeter: 0.312 inches Hole Diameter: 0.312 inches Heavay Diameter: 0.312 inches Horad Diameter: 0.312 inches Hole Diameter: 0.312 inches Hole Quantity: 4 Hole Dype: Dialid Horady Oxy Per Inch (tpi): 14 Horady Oxy Per Inch (tpi
Tread Length: 0.537 inches Fastener Length: Between 1.673 inches and 1.703 inches Head Style: Bevel-conical Head Diameter: Between 0.521 inches and 0.531 inches Head Height: 0.312 inches Head This 0.535 inches Hernal Drive Style: Internal Drive Style: 10.55 inches Internal Drive Style: 10.521 inches Hexagon Thread Diameter: 0.312 inches Hexagon Thread Diameter: 0.312 inches Hole Quantity: 4 Hole Quantity: 5 Ported Diameter: 10.111 inches 11.111 inches 12.111 inches 13.12 inches 14.111 inches 15.111 inches 15.111 inches 16.111 inches 17.111 inches 18.111 inches 19.111 inches 19.111 inches 10.1111 inches 10.1111 inc
0.537 inchesFastener Length:Between 1.673 inches and 1.703 inchesHead Style:Bevel-conicalHead Diameter:Between 0.521 inches and 0.531 inchesHead Height:0.312 inches0.312 inchesHole Diameter:0.055 inchesHoreal Drive Style:Internal Drive Style:10.531 inchesHexagonThread Diameter:0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Duameter:0.312 inchesHole Type:DrilledHoread Quarty:4Hole Type:DrilledInternal ChesHole Type:DrilledHole Stength (psi):160000 pounds per square inch
Fastener Length: Between 1.673 inches and 1.703 inches Head Style: Bevel-conical Head Diameter: Between 0.521 inches and 0.531 inches Head Height: 0.312 inches Hole Diameter: 0.055 inches Internal Drive Style: Hexagon Vidth Across Flats: Betwen 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Diall Jiternal Charter: 0.251 inches Hexagon Thread Diameter: 0.312 inches Hole Quantity: Percence Jiternal Charter Between 0.219 inches and 0.221 inches Hole Quantity: Jiternal Hole Type: Dialled Hourity: Jiternal Hole Type: Dialled Hourity: Jiternal Hole Type: Dialled Hourity: Jiternal Hourity: <
Between 1.6° inches and 1.703 inches Head Style: Bevel-conical Head Diameter: Between 0.521 inches and 0.531 inches Head Height: 0.312 inches Hole Diameter: 0.312 inches Hole Diameter: 0.055 inches Internal Drive Style: Hacagon Thread Diameter: 0.312 inches Width Across Flats: Betwen 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Thready Cty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
Head Style:Bevel-conicalHead Diameter:Between 0.521 inches and 0.531 inchesHead Height:0.312 inchesHole Diameter:0.055 inchesHerral Drive Style:HexagonThread Diameter:0.312 inchesBetween 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Cty Per Inch (tpi):24Hone Strength (psi):160000 pounds per square inch
Bevel-conical Head Diameter: Between 0.521 inches and 0.531 inches Head Height: 0.312 inches Hole Diameter: 0.055 inches Internal Drive Style: Hexagon Thread Diameter: 0.312 inches Width Across Flats: Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Interady Oty Per Inch (tpi): 24 House Type: 14 Intersile Strength (psi): 160000 pounds per square inch
Head Diameter:Between 0.521 inches and 0.531 inchesHead Height:0.312 inches0.312 inchesHole Diameter:0.055 inchesInternal Drive Style:HexagonThread Diameter:0.312 inchesWitch Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Cty Per Inch (tpi):24Honsile Strength (psi):16000 pounds per square inch
Between 0.521 inches and 0.531 inchesHead Height:0.312 inchesJate columeter:0.055 inchesInternal Drive Style:HexagonThread Diameter:0.312 inchesWith Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Uy Per Inch (tpi):24Min. Tensile Strength (psi):16000 pounds per square inch
Head Height:0.312 inchesHole Diameter:0.055 inchesInternal Drive Style:HexagonThread Diameter:0.312 inchesWitch Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Ry Per Inch (tpi):24Honoline Strength (psi):16000 pounds per square inch
0.312 inchesHole Diameter:0.055 inchesInternal Drive Style:HexagonThread Diameter:0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
Hole Diameter:0.055 inchesInternal Drive Style:HexagonThread Diameter:0.312 inchesWith Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledDrilledInterady Cty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
0.055 inches Internal Drive Style: Hexagon Thread Diameter: 0.312 inches 0.312 inches Vidth Across Flats: Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
Internal Drive Style:HexagonThread Diameter:0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledDrilledInternal Qty Per Inch (tpi):24Hone Strength (psi):160000 pounds per square inch
HexagonThread Diameter:0.312 inches0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
Thread Diameter:0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
0.312 inchesWidth Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:4Hole Type:DrilledDrilledAtready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
Width Across Flats:Between 0.219 inches and 0.221 inchesHole Quantity:44Hole Type:DrilledThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
Between 0.219 inches and 0.221 inches Hole Quantity: 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
Hole Quantity: 4 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
4 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
Hole Type:DrilledThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):160000 pounds per square inch
Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch
24 Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch
160000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response

NSN 5306-00-558-2763

Internal Wrenching Bolt - Page 2 of 2



Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.