## NSN 5306-00-558-2822



Internal Wrenching Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-558-2822 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.287 inches and 1.337 inches **Fastener Length:** Between 4.547 inches and 4.577 inches **Head Style:** Bevel-conical **Head Diameter:** Between 1.615 inches and 1.625 inches **Head Height:** 1.000 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 1.000 inches Width Across Flats: Between 0.751 inches and 0.755 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 34.0 rockwell c and 40.0 rockwell c Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** 

Cadmium and chromate

## **Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:** 

Uns

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

## NSN 5306-00-558-2822

Internal Wrenching Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.