## NSN 5306-00-558-6638

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-558-6638 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.760 inches and 0.820 inches **Fastener Length:** 4.690 inches **Head Style:** Hexagon **Head Height:** 0.344 inches Width Between Flats: Between 0.741 inches and 0.750 inches **Hole Diameter:** 0.070 inches First Diameter From Head: Between 0.494 inches and 0.500 inches **Second Diameter From Head:** Between 0.387 inches and 0.391 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.470 inches and 0.530 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 3.870 inches and 3.930 inches **Thread Diameter:** 0.500 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** 

Navy special project

Material:

Steel comp 8740 or steel comp 94b30

## NSN 5306-00-558-6638

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0