

View Online at <https://aerobasegroup.com/nsn/5306-00-558-7682>

Thread Direction:

Right-hand

Thread Length:

Between 0.600 inches and 0.640 inches

Fastener Length:

Between 1.240 inches and 1.260 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.412 inches and 0.432 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

Between 0.090 inches and 0.100 inches

Shoulder Length:

0.620 inches first shoulder and 0.640 inches first shoulder

Shoulder Width Across Flats:

0.435 inches first shoulder

Thread Diameter:

0.375 inches

Nonstandard Thread Pitch Diameter:

+0.3420/+0.3449 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Shoulder Shape:

Hexagonal first shoulder

Material:

Stainless steel

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0